

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-145288

(43)Date of publication of application : 28.05.1999

(51)Int.Cl.

H01L 21/768
H01L 21/304
H01L 21/3205

(21)Application number : 10-081415

(71)Applicant : HITACHI LTD

(22)Date of filing : 27.03.1998

(72)Inventor : OHASHI TADASHI
YAMAGUCHI HIDE
NOGUCHI JUNJI
OWADA NOBUO

(30)Priority


Priority number : 09242825 Priority date : 08.09.1997 Priority country : JP

(54) SEMICONDUCTOR INTEGRATED CIRCUIT DEVICE AND MANUFACTURE THEREOF

(57)Abstract:

PROBLEM TO BE SOLVED: To increase the yield and the reliability of a semiconductor integrated circuit device by preventing a short-circuit defect of a second metal interconnection formed on a first metal interconnection by CPM(chemical mechanical polishing).

SOLUTION: In a semiconductor integrated circuit device, wherein inter-layer insulating films 11a, 11b are formed in an upper part of a semiconductor substrate 1 in which an n-type MISFET Qn is formed, and an interconnection 14 which fills an interconnection recess 14 formed in the interlayer insulating film 11b is formed by depositing a metal film made of copper or the like and polishing it by CMP, an inter-layer insulating film 16 formed on the interconnection 14 and the inter-layer insulating film 11b is constituted of a blocking layer 16a, a planarized layer 16b, and an insulating film 16c. For the planarized layer 16b, a film having a self fluidity such as an SOG(spin-on-glass) film is used.



LEGAL STATUS

[Date of request for examination]

13.03.2003

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]